



PESI – WEIGHTS

PORTATA kg	SUDDIV. g	PESI / WEIGHTS (kg)			
		dinamometro dynamometer	golfare eye nut	gancio hook	grillo shack
300	200	1.4	0.8	0.9	0.6
500	200	1.4	0.8	0.9	0.6

Technical specifications

- Alloy steel extensometric load cell tensile electronic dynamometer
- Linearity and repeatability accuracy: +/- 0.1% (o.f.s.v.)
- Safety degree: 5
- Admitted load: 120%
- Functions: tare re-set, peak and measurement unit selection (kg, daN, Lb, ton)
- Rechargeable battery power supply (36 hour autonomy)
- Battery charger: 220 V a.c. power supply
- Re-charging time: 8 hours
- 25 mm high **LED** display
- Auto-deactivation
- IP 55 protection
- Operating temperature: -10 ÷ +55°C
- No metrical check required

Standard fittings

- Re-chargeable batteries and battery charger
- Infra-red remote control
- Collar upper connection and revolving hook or shackle in the lower part
- SIT Reference calibration report
- EC conformity declaration

Remote control functions

- Tare re-set
- Peak function
- Measurement unit selection (kg, daN, Lb, ton)



CAMI S.r.l.

MEASUREMENT TOOLS PROJECTING AND MANUFACTURING

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

www.cami-it.com - e-mail camipa@tin.it

