



DIN 102 TSG				
PORTATA [kg]	DIVISIONE [g]	PESO [kg]	DIMENSIONI [mm]	
			A	B
1000	500	5	340	370
2000	500	5	360	390

Technical specifications

- Load cell tensile electronic dynamometer fitted with revolving hook on bearings
- Linearity and repeatability accuracy: +/- 0.1% (o.f.s.v.)
- Safety degree: 5
- Admitted overload: 120%
- Functions: tare re-set, peak and measurement selection (kg, daN, Lb, ton)
- Display double brightness function
- Re-chargeable battery power supply (continuous 50 hour autonomy)
- 25 mm high red LED 5 digit display
- Automatic stand-by and auto-deactivation
- IP 55 protection
- Operating temperature: -10 ÷ +55°C
- Nylon and glass fibre case for aggressive environments
- No metrical check required

Standard fittings

- Re-chargeable batteries and battery charger
- Infra-red remote control
- SIT reference calibration report
- EC conformity declaration

Fittings on request

- Rs232 serial port
- Remote repeater
- Case



CAMI S.r.l.

MEASUREMENT TOOLS PROJECTING AND MANUFACTURING

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

www.cami-it.com - e-mail camipa@tin.it