



DIN105TSL

PORTATA [kg]	DIVISIONE [kg]	PESO [kg]	DIMENSIONI [mm]				
			A	B	C	D	E
2000	1	2,6	206	70	166	306	18
3200	1	3,2	206	70	166	306	25
6300	2	4,8	224	70	166	360	34
10000	5	8,6	270	100	188	462	49
25000	10	12,8	370	100	257	665	49

Technical specifications

- Steel Load cell tensile electronic dynamometer
- Linearity and repeatability accuracy: +/- 0.1% (o.f.s.v.)
- Safety degree: 5
- Admitted overload: 120%
- Tare reset function
- Battery test
- Re-chargable battery supply (50 hour autonomy)
- 25 mm high red LCD 5 digit display
- Programmable stand-by and auto-deactivation
- IP 55 protection
- Operating temperature: -10 ÷ +55°C
- Nylon and glass fibre case for aggressive environment
- No metrical check required

Standard fittings

- Re-chargable batteries and battery charger
- Radio remote control
- Case (up to 10.000 kg)
- Box (for 20 and 25 T)
- SIT reference calibration report
- EC conformity declaration

Accessories on request

- Omega shackle (Crosby® type) and hook
- Revolving hooks fitted with shackle connection
- Rs232 serial port
- Remote repeater



CAMI S.r.l.

PROGETTAZIONE E COSTRUZIONE STRUMENTI DI MISURA

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

www.cami-it.com - e-mail camipa@tin.it