



DIN 12						
PORTATA [kg]	DIVISIONE [kg]	PESO [kg]	DIMENSIONI [mm]			
			A	∅B	C	D
300	2	6	192	20	74	25
500	3	6	192	20	74	25
1000	5	6	192	20	74	25
2000	10	6	192	20	74	25
3000	20	6	192	20	74	25
6000	25	11	206	26	98	35
10000	50	11	222	36	98	50

### Technical specifications

- Steel elastic cell tensile mechanical dynamometer
- Compact and small size instrument
- For external use
- Operating temperature:  $-30 \div +60^{\circ}\text{C}$
- Painted aluminium case
- DN 100 mm analogue dial
- Omega shackle connections (tensile version)
- Admitted overload: up to 180% of full scale value
- Linearity and repeatability accuracy:  $\pm 1\%$  (o.f.s.v.)
- Safety degree: 5
- No metrical check required

### Standard fittings

- SIT Reference calibration report
- EC conformity declaration

### Accessories on request

- Maximum index
- "OMEGA" shackle
- Hinged hook fitted with shackle connections
- Bag to carry the instrument



**CAMI S.r.l.**

**MEASUREMENT TOOLS PROJECTING AND MANUFACTURING**

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

[www.cami-it.com](http://www.cami-it.com) - e-mail [camipa@tin.it](mailto:camipa@tin.it)