



DIN 13							
PORTATA [kg]	DIVISIONE [kg]	PESO [kg]	DIMENSIONI [mm]				
			A	B	∅C	D	E
1000	2	8	268	25	20	155	134
2000	5	8	268	25	20	155	134
3000	10	8	268	25	20	155	134
6000	20	13	282	35	26	179	158
10000	20	13	298	50	36	179	158

Technical specifications

- Tensile mechanical dynamometer fitted with forged steel elastic cell
- For external use
- Operating temperature: $-30 \div +60^{\circ}\text{C}$
- Painted aluminium case
- Transparent, made up of polycarbonate
- DN 200 mm analogue dial
- Omega shackle connections
- Zero manual adjustment
- Admitted overload: up to 180% of full scale value
- Accuracy: $\pm 1\%$ (o.f.s.v.)
- Safety degree: 5
- No metrical check required

Standard fittings

- SIT Reference calibration report
- EC conformity declaration

Accessories on request

- Maximum index
- "OMEGA" shackles
- Hinged hook fitted with shackle connections



CAMI S.r.l.

MEASUREMENT TOOLS PROJECTING AND MANUFACTURING

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

www.cami-it.com - e-mail camipa@tin.it

