



Portata (kg)	A	B	C	D	E	F	G	H	Peso (kg)
100	84	84	45	6.5	70	70	10	20	2.4
250	84	84	45	6.5	70	70	10	20	2.4
500	84	84	45	6.5	70	70	10	20	2.4
1000	84	84	45	6.5	70	70	10	20	2.4
2500	110	110	50	9	90	90	15	25	3.8
5000	110	110	50	9	90	90	15	25	3.8
10000	110	110	50	9	90	90	15	25	3.8
20000	110	110	50	9	90	90	15	25	3.8

General description

- Compression electronic dynamometer fitted with load cell and digital display. Connection between load cell and display through cable. Rechargeable battery operation. The instrument is provided with Calibration Report

Load cell features

- Ranges: from 100 to 20.000 kg
- Material: stainless steel
- Combined error: $\pm 0.1\%$ o.f.s.v.
- Repeatability: $\pm 0.05\%$ o.f.s.v.
- Temperature shifts: $\pm 0.005\%$ f.s./ $^{\circ}\text{C}$
- Temperature compensation fields : $-10 \div +50^{\circ}\text{C}$
- Full load creep : 0.03% s.v. (20')
- Admitted overload: 150% s.v.
- Breakage load: >300% s.v.
- Protection grade: IP67
- Maximum arrow: 0.3 mm a s.v.
- Connection cable: 4 metres

Display features

- Nylon case fitted with handle
- 25 mm high 5 digit LED display
- 50 hour re-chargeable batteries autonomy
- Auto-deactivation
- Measurement unit selection
- Tare re-set function
- Peak function
- RS232 serial transmission (on request)



CAMI S.r.l.

MEASUREMENT TOOLS PROJECTING AND MANUFACTURING

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

www.cami-it.com - e-mail camipa@tin.it