

# DIN 107 E- X

## Stainless Steel Electronic Dynamometer with load cell - Traction working

### Characteristics

- Capacities: 5; 10; 20; 50 kg
- Division: 3000 div. on Full scale value
- Display: 4 digit Led height 14 mm
- Power supply: rechargeable batteries
- Autonomy: 36 hours
- Functions: zero tare, peak, Auto Off
- Case: Stainless Steel – AISI 304
- Inner parts: Stainless Steel
- Connections: Stainless Steel Revolving eyebolts
- Inner Parts: Stainless Steel
- Accuracy: 0.1% f.s.
- Overload Admitted: 120% f.s.
- Safety Factor: 5
- Working Temperature: -10 ÷ +60 °C
- Protection IP: 65

### Standard Equipment

- Power Pack: 220 V 50/60 Hz
- Calibration Certificate
- EC Calibration
- User manual

### Fittings on request

- Suitcase



**CAMI S.r.l.**

**MEASUREMENT INSTRUMENTS**

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

[www.cami-it.com](http://www.cami-it.com) - e-mail [info@cami-it.com](mailto:info@cami-it.com)