

# DIN 109 CT

## Electronic dynamometer with Load Cell CT traction / compression working

### Features

- Capacities: from 5 kg to 10 ton
- Display: graphic LCD 60 x 30 mm
- Supply: rechargeable battery set
- Autonomy: 36 hours
- Functions: tare reset, peak  
Auto Off selectable,  
Digital filter,  
Measurement recording with  
Down Load via USB
- Load cell connection: by 4 meters wire with  
MIL connector plug
- Accuracy: 0.1% s.v.f.s.
- Over Load: 120% f.s.
- Load cell safety factor: 3
- Working Temperature: -10 ÷ +60 °C
- Protection degree: IP55 (display) ;  
IP 66 (load cell)

### Standard equipment

- Battery charger 220 V 50/60 Hz
- Calibration Certificate
- CE declaration certificate
- User manual

### Special execution

With high frequency recording function  
for high speed dynamometric tests .  
Frequency: 2 MHz



**Dynamometer DIN109 is  
available with a large  
catalogue of load cells**

**See the technical data  
sheet of CT Load cell  
for more details.**

**CAMI S.r.l.**

**MEASUREMENT INSTRUMENTS**

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

[www.cami-it.com](http://www.cami-it.com) - e-mail [info@cami-it.com](mailto:info@cami-it.com)